

View Online at <https://aerobasegroup.com/nsn/5935-00-433-6128>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.078 inches and 1.110 inches

Overall Diameter:

Between 0.677 inches and 0.697 inches

Environmental Protection:

Heat resistant and moisture resistant and vibration resistant

Cable Entrance Diameter:

Between 0.115 inches and 0.120 inches

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

28

Thread Size:

0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces silver

Precious Material And Weight:

0.105 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0