NSN 5935-00-434-3212

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-434-3212

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 1.375 inches |
| Overall Diameter: |
| Between 1.170 inches and 1.180 inches |
| Environmental Protection: |
| Explosion proof and heat resistant and moisture proof and vibration resistant |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 14-15 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Key, multiple key groove |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Thready Qty Per Inch (tpi): |
| 36 |
| Thread Size: |
| 0.803 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Rhodium single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |

Stainless steel

NSN 5935-00-434-3212Electrical Plug Connector - Page 2 of 2



| Shell Surface Treatment: |
|---|
| Passivate |
| Shell Surface Treatment Specification: |
| Mil-std-171 military standard single treatment response |
| Included Contact Quantity: |
| 15 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces rhodium |
| Precious Material And Weight: |
| 0.015 rhodium grains, troy |
| Precious Material: |
| Rhodium |
| Test Data Document: |
| 81349-mil-c-26500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Uns |
| Specification Data: |
| 96906-ms27615 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-std-171 spec. |
| |