

View Online at https://aerobasegroup.com/nsn/5935-00-435-0559

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, rectangular |
| Overall Length: |
| 2.730 inches |
| Overall Height: |
| 0.870 inches |
| Overall Width: |
| Between 1.992 inches and 2.008 inches |
| Environmental Protection: |
| Vibration resistant and moisture resistant and thermal shock resistant and corrosion resistant |
| Unthreaded Mounting Hole Diameter: |
| Between 0.112 inches and 0.132 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.468 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.688 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 55 single mating end |
| Polarization Method: |
| Guide pin/socket |
| Connector Locking Method: |
| Jackscrew |
| Thread Length: |
| 0.440 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Insert Material: |
| Plastic diallyl phthalate glass filled single mating end |
| Guide Design And Location: |
| Hexagon shape male post right-hand at 11 oclock |
| Insert Material Specification: |
| Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single material response single mate |
| material response single mating end |



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.