NSN 5935-00-435-0572



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-435-0572 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/jackscrew **Overall Length:** Between 1.992 inches and 2.008 inches **Overall Height:** 2.730 inches **Overall Width:** 0.870 inches **Environmental Protection:** Thermal shock resistant and moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.112 inches and 0.132 inches **Distance Between Mounting Facility Centers:** 1.688 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** 2 polarization posts **Connector Locking Method:** Jackscrew Thread Length: 0.440 inches Thready Qty Per Inch (tpi): 32 **Thread Size:**

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-00-435-0572

Electrical Receptacle Connector - Page 2 of 2



Insert Material:

Glass single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c or d, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-750, composition a federal specification single material response single mating end single contact grouping

Guide Design And Location:

Hexagon shape male post right-hand at 7 oclock

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30f military specification all material responses single mating end

Included Contact Quantity:

55 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.055 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.