Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-435-3963

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
2.750 inches
Overall Diameter:
1.594 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Cable Entrance Diameter:
0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-7 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
245.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1750.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp w/telescoping bushing
Thready Qty Per Inch (tpi):
Thread Size:
1.375 inches

## NSN 5935-00-435-3963 Electrical Plug Connector - Page 2 of 2



	nal Location:
	ingle mating end single contact grouping
	ct Material:
	alloy single mating end single contact grouping
	ct Surface Treatment:
	single mating end single contact grouping
	Material:
	single mating end
	ct Surface Treatment Specification:
	65 federal specification single treatment response single mating end single contact groupin
	nal Type:
	single mating end single contact grouping
-	faterial:
	um alloy
	Surface Treatment:
	um and chromate
	ed Contact Quantity:
	e mating end single contact grouping
	ed Contact Type:
	socket single mating end single contact grouping us Material And Location:
	t surfaces silver
	us Material And Weight:
	silver grains, troy
	us Material:
Silver	
	I Series Designator:
Unef	
Shelf L	ife:
N/a	
	f Measure:
Demili	tarization:
No	
Fiig:	
A039b0	