

View Online at <https://aerobasegroup.com/nsn/5935-00-436-0785>

Body Style:

Straight shape quick connect

Overall Length:

0.671 inches

Overall Width:

0.145 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Mounting Facility Thickness:

0.275 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type class military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-b-626, comp 22 half hard federal specification single material response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Copper

Shell Surface Treatment Specification:

Mil-c-14550, cl 4 military specification single treatment response

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.