

View Online at <https://aerobasegroup.com/nsn/5935-00-436-0916>

Body Style:

Straight shape, external coupling

Overall Length:

1.120 inches

Overall Diameter:

1.630 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

20-92 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

250.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2 class 3 federal specification 1st treatment response

Shell Material Specification:

Mil-c-26482 military specification single material response

Insert Material Specification:

Mil-m-14, type sdc-f military specification single material response single mating end

Included Contact Quantity:

92 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Grommet

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.092 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.