## NSN 5935-00-436-2295

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-436-2295

**Body Style:** Straight shape, rectangular **Overall Length:** 1.219 inches **Overall Height:** 0.562 inches **Overall Width:** 0.375 inches **Environmental Protection:** Vibration resistant **Unthreaded Mounting Hole Diameter:** 0.094 inches **Distance Between Mounting Facility Centers:** 0.905 inches **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping and gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-f-14072 military specification 1st treatment response single mating end single contact grouping and mil-g-43204, type ii, class i military specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Insert Material Specification:** 

Mil-m-14, type sdi-5 military specification single material response single mating end

### **Included Contact Quantity:**

7 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contacts silver and contacts gold

# NSN 5935-00-436-2295

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:	
0.007 silver grains, troy and 0.007 gold grains, troy	
Precious Material:	
Silver and gold	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
Δ030h0	

Mil-std (military Standard):

Mil-f-14072 spec.