## NSN 5935-00-436-2602

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-436-2602 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape quick connect **Overall Length:** 0.700 inches **Overall Width:** 0.375 inches **Environmental Protection:** Moisture resistant and vibration resistant and hermetic **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Rf all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Current Rating In Amps:** 1.5 all mating ends single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 all mating ends single contact grouping **Contact Maximum Frequency Rating:** 10000.0 megahertz all mating ends single contact grouping Shell Type: Solid **Connector Locking Method:** Spring friction Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** 

Gold all mating ends single contact grouping

**Insert Material:** 

Glass all mating ends

## NSN 5935-00-436-2602

Connector Adapter - Page 2 of 2

No Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.



## **Contact Surface Treatment Specification:** Mil-g-45204, type 2, cl 2 military specification single treatment response all mating ends single contact grouping **Contact Material Specification:** Qq-b-626, comp 22 federal specification single material response all mating ends single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Gold **Shell Surface Treatment Specification:** Mil-g-45204, type 2, cl 2 military specification single treatment response **Shell Material Specification:** Qq-b-626, comp 22 federal specification single material response **Included Contact Quantity:** 1 all mating ends single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Coaxial pin all mating ends single contact grouping **Precious Material And Location:** Contact and shell surfaces gold **Precious Material And Weight:** 0.110 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**