## NSN 5935-00-436-2602

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-436-2602

View Online at https://aerobasegroup.com/nsn/5935-00-436-2602
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape quick connect
Overall Length:
0.700 inches
Overall Width:
0.375 inches
Environmental Protection:
Moisture resistant and vibration resistant and hermetic
Threaded Device Type:
Mounting bushing
Mating End Quantity:
2
Contact Position Arrangement Style:
Rf all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Contact Maximum Current Rating In Amps:
1.5 all mating ends single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
400.0 all mating ends single contact grouping
Contact Maximum Frequency Rating:
10000.0 megahertz all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Spring friction
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 all mating ends single contact grouping
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping
Insert Material:

Glass all mating ends

## NSN 5935-00-436-2602

Connector Adapter - Page 2 of 2



**Contact Surface Treatment Specification:** Mil-g-45204, type 2, cl 2 military specification single treatment response all mating ends single contact grouping **Contact Material Specification:** Qq-b-626, comp 22 federal specification single material response all mating ends single contact grouping Shell Material: Copper alloy **Shell Surface Treatment:** Gold **Shell Surface Treatment Specification:** Mil-g-45204, type 2, cl 2 military specification single treatment response **Shell Material Specification:** Qq-b-626, comp 22 federal specification single material response **Included Contact Quantity:** 1 all mating ends single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Coaxial pin all mating ends single contact grouping **Precious Material And Location:** Contact and shell surfaces gold **Precious Material And Weight:** 0.110 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.