

View Online at <https://aerobasegroup.com/nsn/5935-00-437-5324>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

3.125 inches

**Overall Height:**

0.719 inches

**Overall Width:**

0.375 inches

**Distance Between Mounting Facility Centers:**

Between 2.790 inches and 2.810 inches

**Threaded Device Type:**

Mounting stud

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

2.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

130.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic phenolic single mating end

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-p-79, form tr, type pbm military specification single material response single mating end

**Included Contact Quantity:**

50 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold and contact surface silver

**Precious Material And Weight:**

0.050 gold grains, troy and 0.050 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-p-79 spec.