Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-437-6472

#### **Body Style:**

Straight edge type w/mounting flange

**Overall Length:** 

3.256 inches

# **Overall Height:**

0.500 inches

**Overall Width:** 

0.590 inches

#### **Unthreaded Mounting Hole Diameter:**

Between 0.151 inches and 0.161 inches

### **Distance Between Mounting Facility Centers:**

Between 2.868 inches and 2.884 inches

## **Board Accommodated Length:**

2.286 inches single board

### **Board Accommodated Width:**

0.070 inches

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

1 row of contacts inserted board single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

# Contact Maximum Current Rating In Amps:

16.0 single mating end single contact grouping

# Contact Maximum Ac Voltage Rating In Volts:

2200.0 single mating end single contact grouping

### **Polarization Method:**

Contact to contact polarizing keys

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic single mating end

### **Terminal Type:**

Solder well single mating end single contact grouping

### Included Contact Quantity:

15 single mating end single contact grouping

### **Included Contact Type:**

Spring pincers single mating end single contact grouping



Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.015 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --

No

Fiig:

A039b0