

View Online at <https://aerobasegroup.com/nsn/5935-00-439-3737>

Body Style:

Right angle, card

Overall Length:

3.514 inches

Body Width:

Between 0.360 inches and 0.380 inches

Body Height:

Between 0.302 inches and 0.322 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1800.0 single mating end single contact grouping

Connector Locking Method:

Spring friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdgf military specification single material response single mating end

Included Contact Quantity:

35 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.035 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.