

View Online at <https://aerobasegroup.com/nsn/5935-00-442-1993>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/strain relief

Overall Length:

1.375 inches

Overall Diameter:

0.688 inches

Environmental Protection:

Weatherproof

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

50.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cord protector

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

28

Thread Size:

0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold and shell surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0