## NSN 5935-00-442-6513

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-442-6513

**Body Style:** 

Angle shape w/cable clamp

**Overall Diameter:** 

2.470 inches

**Body Angle In Deg:** 

90.0

**Cable Entrance Diameter:** 

1.375 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

36-8 single mating end

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

41.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:** 

700.0 single mating end all contact groupings

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

80.0

Shell Type:

Solid

**Connector Cable Strain Relief Method:** 

Cable clamp

**Distance From Centerline To Connector End:** 

3.061 inches

**Distance From Centerline To Cable End:** 

6.016 inches

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Silver single mating end all contact groupings

**Insert Material:** 

Rubber single mating end

**Contact Surface Treatment Specification:** 

Qq-s-365 federal specification single treatment response single mating end all contact groupings

## **NSN 5935-00-442-6513**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Pin single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
46 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.047 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0