

View Online at <https://aerobasegroup.com/nsn/5935-00-443-4232>

Body Style:

Straight shape, external coupling

Overall Length:

1.109 inches

Overall Height:

1.188 inches

Overall Width:

1.188 inches

Environmental Protection:

Moisture resistant and vibration resistant and shock resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

Distance From Mounting Shoulder To Front Face:

0.531 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

19-2p single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

2000.0 single mating end 2nd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

2500.0 single mating end 2nd contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Plastic silicone single mating end

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

9 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 2nd contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0