NSN 5935-00-443-7318

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-443-7318 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.093 inches **Overall Height:** 0.812 inches **Overall Width:** 0.812 inches **Environmental Protection:** Moisture resistant and vibration resistant and fuel proof **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.625 inches **Distance From Mounting Shoulder To Front Face:** 0.624 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 3 number 16 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 20.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 150.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-00-443-7318

Electrical Receptacle Connector - Page 2 of 2



Thread Length:
0.400 inches
Thread Size:
0.625 inches and 0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.003 gold grains, troy and 0.003 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A039b0