NSN 5935-00-443-8327

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-443-8327 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.160 inches and 1.200 inches **Overall Height:** Between 1.120 inches and 1.130 inches **Overall Width:** Between 1.120 inches and 1.130 inches **Unthreaded Mounting Hole Diameter:** 1.121 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 14-7 single mating end **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.938 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Iron alloy single mating end single contact grouping **Contact Surface Treatment:** Nickel single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-c-26074, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:**

Tab, solder lug single mating end single contact grouping

NSN 5935-00-443-8327

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:

Mil-i-23011, class 2 military specification single material response single mating end single contact grouping

Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-i-23011 spec.