NSN 5935-00-443-9441

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-443-9441 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.172 inches **Overall Diameter:** 1.406 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 16-26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch **Thread Size:** 0.938 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy

Cadmium

Shell Surface Treatment:

NSN 5935-00-443-9441

A039b0

Mil-std (military Standard):

Mil-c-27599 spec.

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Contact designation 17-26
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
0.026 gold grains, troy and 0.026 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-27599 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms20028 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: