

View Online at <https://aerobasegroup.com/nsn/5935-00-444-0072>

**Body Style:**

Straight shape w/flange

**Overall Length:**

1.604 inches

**Overall Height:**

Between 1.021 inches and 1.042 inches

**Overall Width:**

Between 1.021 inches and 1.042 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.123 inches and 0.133 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.812 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.812 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.632 inches and 0.637 inches

**Mating End Quantity:**

2

**Contact Maximum Current Rating In Amps:**

5.0 all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

400.0 all mating ends single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

550.0 all mating ends single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Included Contact Quantity:**

13 all mating ends single contact grouping

**Included Contact Type:**

Round socket 2nd mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.026 gold grains, troy and 0.026 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0