## NSN 5935-00-444-0197

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-444-0197 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.125 inches **Overall Height:** Between 0.490 inches and 0.510 inches **Overall Width:** 0.468 inches **Distance Between Mounting Facility Centers:** 0.750 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 14 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Friction Thread Length: 0.180 inches Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Stainless steel single mating end single contact grouping

## NSN 5935-00-444-0197

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold and copper and nickel single mating end single contact grouping
Insert Material:
Glass single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Gold and copper and nickel
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact and body surfaces gold
Precious Material And Weight:
0.114 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A039b0