

View Online at <https://aerobasegroup.com/nsn/5935-00-444-1243>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.243 inches

**Overall Diameter:**

Between 1.484 inches and 1.516 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Distance From Mounting Shoulder To Front Face:**

Between 0.910 inches and 0.920 inches

**Mounting Facility Thickness:**

Between 0.062 inches and 0.125 inches

**Threaded Device Type:**

Back shell and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

13-98 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Thready Qty Per Inch (tpi):**

24 and 20

**Thread Size:**

0.687 inches and 1.000 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

10 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold and contact surface silver

**Precious Material And Weight:**

0.010 gold grains, troy and 0.010 silver grains, troy

**Precious Material:**

Gold and silver

**Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef and unef

**Specification Data:**

81349-mil-c-38999 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0