Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-444-8413

| Thread Class   |
|--|
| Thread Class:  |
|  |
| Thread Direction:  |
| Right-hand   |
| Body Style:  |
| Straight shape, external coupling  |
| Overall Length:  |
| 0.562 inches   |
| Overall Diameter:  |
| 0.281 inches   |
| Threaded Device Type:  |
| Back shell   |
| Mating End Quantity:   |
|  |
| Contact Removability:  |
| Nonremovable single mating end single contact grouping   |
| Polarization Method:   |
| Contact  |
| Shell Type:  |
| Solid  |
| Connector Locking Method:  |
|  |
| Thread Length:   |
|  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Thread Size:   |
| 0.250 inches   |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping Insert Material:  |
|  |
| Plastic single mating end  |
| Contact Surface Treatment Specification:   |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type:   |
| Solder well single mating end single contact grouping  |
| Shell Material:  |
| Plastic  |

## NSN 5935-00-444-8413

Electrical Plug Connector - Page 2 of 2



**Included Contact Quantity:** 3 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.015 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.