## NSN 5935-00-445-3378

**Body Style:** 

Straight shape, external coupling

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-445-3378

Overall Length:	
0.887 inches	
Overall Height:	
1.250 inches	
Overall Width:	
1.250 inches	
Unthreaded Mounting Hole Diameter:	
0.150 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
0.938 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
0.938 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.462 inches and 0.472 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
12-10 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
7.5 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
500.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
700.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	
Shell Type:	
Solid	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and silver single mating end single contact grouping	
Terminal Type:	
Solder well single mating end single contact grouping	

## NSN 5935-00-445-3378

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
10 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.010 gold grains, troy and 0.010 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0