## NSN 5935-00-445-6474

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-445-6474 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.964 inches **Overall Diameter:** Between 2.589 inches and 2.599 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 8 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring Thread Length: 0.499 inches Thready Qty Per Inch (tpi): 16 and 10 **Thread Size:** 2.250 inches and 2.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping

Insert Material:

Plastic single mating end

## NSN 5935-00-445-6474

Demilitarization:

No Fiig: A039b0

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment Specification:
Qq-s-365, type 3, gr b federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
8 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.008 silver grains, troy
Precious Material:
Silver
Test Data Document:
10001-2661791 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Uns and double stub
Specification Data:
10001-2661791 manufacturers specification
Shelf Life:
N/a
Unit Of Measure: