NSN 5935-00-449-6708

Electrical Receptacle Connector - Page 1 of 2

Bifurcated spring single mating end single contact grouping



View Online at https://aerobasegroup.com/nsn/5935-00-449-6708

Body Style:
Straight type
Overall Length:
3.460 inches
Overall Height:
0.360 inches
Overall Width:
1.265 inches
Unthreaded Mounting Hole Diameter:
0.139 inches
Distance Between Mounting Facility Centers:
2.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
250.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
300.0 single mating end single contact grouping
Polarization Method:
Mating end
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a hard federal specification single material response single mating end single contact grouping
Included Contact Quantity:
44 single mating end single contact grouping
Included Contact Type:

NSN 5935-00-449-6708 Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0