

View Online at https://aerobasegroup.com/nsn/5935-00-449-6784

Thi	read	CI	ass:

2a and 2b and 2a

**Thread Direction:** 

Right-hand

**Body Style:** 

Rectangular shape

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.984 inches

**Overall Height:** 

0.930 inches

**Overall Width:** 

1.688 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.500 inches

**Distance Between Mounting Facility Centers:** 

1.969 inches

Threaded Device Type:

Coupling facility and mounting stud

### Mating End Quantity:

1

**Contact Position Arrangement Style:** 

66 single mating end

# **Polarization Method:**

Jackscrew and shell

Shell Type:

Solid

**Connector Locking Method:** 

Jackscrew-socket

# Thready Qty Per Inch (tpi):

32 and 40

Thread Size:

0.138 inches and 0.112 inches

# **Insert Material:**

Plastic diallyl phthalate single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Electrical Receptacle Connector Body - Page 2 of 2



Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Shell Guide Type And Location Designator:

B slot

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.