Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-450-3423

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
2.312 inches
Overall Height:
0.797 inches
Overall Width:
0.750 inches
Distance Between Mounting Facility Centers:
2.000 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
42 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1100.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1500.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Jackscrew-socket
Thread Length:
0.266 inches
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

NSN 5935-00-450-3423

Electrical Receptacle Connector - Page 2 of 2



Insert Material: Plastic phenol-formaldehyde single mating end **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:** 42 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.042 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0