No

Electrical Connector Backshell - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-450-5116

2b Thread Direction: Right-hand Seal Material: Rubber Furnished Items: Strap Overall Longth: 2.500 inches Overall Height: Any acceptable Overall Width: Any acceptable Overall Width: Any acceptable Oxerall Width: Any acceptable Cable Opening Diameter: O.750 inches Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Tyread Size: 1.000 inches Material: Autorial Quidation Stridec Treatment: Cadmium Stridec Treatment: Cadmium </th <th>Thread Class:</th> <th></th>	Thread Class:	
Right-hand Sel Material: Rubber Furnished Items: Strap Overall Length: 2.500 inches Overall Height: Any acceptable Overall Width: Any acceptable Outper Diameter: 0.750 inches Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Stright type wicable clamp Surface Treatment: Cadmium Thread Series Designator: Striface Treatment: Cadmium Sheries Designator: Striface Treatment: Cadmium Sheries Designator: Striface Treatment: Cadmium Sheries Designator: Striface Treatment: Cadmium	2b	
Seal Material: Rubber Furnished Items: Strap Overall Length: 2.500 inches Overall Height: Any acceptable Overall Width: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Sheff Life: Na	Thread Direction:	
Rubber Furnished Items: Strap Overall Length: 2.500 inches Overall Height: Any acceptable Overall Width: Any acceptable Overall Width: Any acceptable Outerall Width: Any acceptable Cable Opening Diameter: 0.750 inches Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Na	Right-hand	
Furnished Items: Strap Overall Length: 2.500 inches Overall Height: Any acceptable Overall Width: Any acceptable Outerall Width: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Striaght type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Sheff Life: Na	Seal Material:	
Strap Overall Length: 2.500 inches 2.500 inches Overall Height: Any acceptable Overall Width: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Cadmium Chread Series Designator: Un Sheif Life: N/a	Rubber	
Overall Length:2:500 inchesOverall Height:Any acceptableOverall Width:Any acceptableCable Opening Diameter:0.750 inchesCable Opening Quantity:1Seal Type:Preformed packingMounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.000 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStriaght type w/cable clampSurface Treatment:CadmiumThread Stries Designator:UnSheft Life:Na	Furnished Items:	
2.500 inches Overall Height: Any acceptable Overall Width: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Straight type w/cable clamp Surface Treatment: Cadmium Thread Steres Designator: Un Sheff Life: Na	Strap	
Overall Height:Any acceptableOverall Width:Any acceptableCable Opening Diameter:0.750 inchesCable Opening Quantity:1Seal Type:Preformed packingMounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.000 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/cable clampSurface Treatment:CadmiumSheries Designator:UnSheff Life:Na	Overall Length:	
Any acceptable Overall Width: Any acceptable Cable Opening Diameter: Cable Opening Diameter: O.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Striaght type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Sheff Life: N/a	2.500 inches	
Overall Width: Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Striaght type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Sheff Life: Na	Overall Height:	
Any acceptable Cable Opening Diameter: 0.750 inches Cable Opening Quantity: 1 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Straight type w/cable clamp Thread Series Designator: Un Shelf Life: Na	Any acceptable	
Cable Opening Diameter:0.750 inchesCable Opening Quantity:11Seal Type:Preformed packingMounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.000 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStyle Designator:Striaght type w/cable clampSurface Treatment:CadmiumShef Life:Na	Overall Width:	
0.750 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	Any acceptable	
Cable Opening Quantity: 1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Intread Series Designator: Un Sheff Life: N/a	Cable Opening Diameter:	
1 Seal Type: Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Straight type model clamp Surface Treatment: Cadmium Straight type model clamp Surface Treatment: Cadmium Surface Treatment: Cadmium Mure model Surface Treatment: Cadmium Mure model	0.750 inches	
Seal Type: Preformed packing Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	Cable Opening Quantity:	
Preformed packing Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Strlaight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	1	
Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.000 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/cable clampSurface Treatment:CadmiumIt type w/cable clampSurface Treatment:CadmiumStufface Treatment:CadmiumSurface Treatment:CadmiumSurface Treatment:CadmiumSurface Treatment:NaNa	Seal Type:	
1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	Preformed packing	
Thready Qty Per Inch (tpi): 28 Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	Mounting Facility Type An	d Quantity:
28 Thread Size: 1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	1 threaded coupling	
Thread Size:1.000 inchesMaterial:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/cable clampSurface Treatment:CadmiumThread Series Designator:UnShelf Life:N/a	Thready Qty Per Inch (tpi)	:
1.000 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	28	
Material:Aluminum alloySurface Treatment:CadmiumStyle Designator:Straight type w/cable clampSurface Treatment:CadmiumThread Series Designator:UnShelf Life:N/a	Thread Size:	
Aluminum alloy Surface Treatment: Cadmium Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	1.000 inches	
Surface Treatment:CadmiumStyle Designator:Straight type w/cable clampSurface Treatment:CadmiumThread Series Designator:UnShelf Life:N/a	Material:	
Cadmium Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	Aluminum alloy	
Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	Surface Treatment:	
Straight type w/cable clamp Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	Cadmium	
Surface Treatment: Cadmium Thread Series Designator: Un Shelf Life: N/a	Style Designator:	
Cadmium Thread Series Designator: Un Shelf Life: N/a	Straight type w/cable clamp	
Thread Series Designator: Un Shelf Life: N/a	Surface Treatment:	
Un Shelf Life: N/a	Cadmium	
Shelf Life: N/a	Thread Series Designator:	
N/a	Un	
	Shelf Life:	
Unit Of Measure:	N/a	
	Unit Of Measure:	
	Demilitarization:	

NSN 5935-00-450-5116

Electrical Connector Backshell - Page 2 of 2

Fiig: A10100

