Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-450-5169



**Thread Class:** 2b **Thread Direction: Right-hand Body Style:** Straight shape, internal coupling **Overall Length:** 2.125 inches **Overall Diameter:** 1.469 inches **Threaded Device Type:** Coupling facility Mating End Quantity: 1 **Contact Position Arrangement Style:** 20-7 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 22.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end 2nd contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 80.0 Shell Type: Potting **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): 18 Thread Size: 1.250 inches **Terminal Location:** Back single mating end all contact groupings **Contact Surface Treatment:** 

Gold single mating end all contact groupings and silver single mating end all contact groupings

## NSN 5935-00-450-5169

Electrical Plug Connector - Page 2 of 2



**Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and silver **Included Contact Quantity:** 4 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.008 gold grains, troy and 0.008 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0