NSN 5935-00-451-5594

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-451-5594 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.250 inches **Overall Height:** 0.609 inches **Overall Width:** 0.281 inches **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 26 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Nickel and gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-00-451-5594

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, sdg-f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.026 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.