

View Online at <https://aerobasegroup.com/nsn/5935-00-451-5714>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, flush mount

**Overall Length:**

Between 1.490 inches and 1.510 inches

**Overall Height:**

Between 4.615 inches and 4.635 inches

**Overall Width:**

Between 3.365 inches and 3.385 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.995 inches and 1.005 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 3.035 inches and 3.045 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.115 inches and 0.135 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

A45 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

30.0 2nd mating end 1st contact grouping

**Polarization Method:**

2 polarization posts

**Shell Type:**

Solid

**Connector Locking Method:**

Screw

**Thready Qty Per Inch (tpi):**

12

**Thread Size:**

0.3125 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Insert Material:**

Plastic silicone single mating end

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

43 2nd mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.090 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0