## NSN 5935-00-451-5715

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-451-5715 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.365 inches and 1.385 inches **Overall Height:** Between 4.240 inches and 4.260 inches **Overall Width:** Between 3.365 inches and 3.385 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.995 inches and 1.005 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 3.035 inches and 3.045 inches **Distance From Mounting Shoulder To Front Face:** Between 0.802 inches and 0.822 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 45 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 30.0 2nd mating end 1st contact grouping **Polarization Method:** 2 polarization posts Shell Type: **Connector Locking Method:** Screw Thready Qty Per Inch (tpi): 12 **Thread Size:** 0.312 inches **Terminal Location:** 

**Contact Material:** 

Copper alloy single mating end all contact groupings

Back single mating end all contact groupings

## NSN 5935-00-451-5715

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic silicone single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
43 2nd mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.090 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0