

View Online at <https://aerobasegroup.com/nsn/5935-00-451-5716>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, flush mount

Overall Length:

Between 1.490 inches and 1.510 inches

Overall Height:

Between 4.615 inches and 4.635 inches

Overall Width:

Between 3.365 inches and 3.385 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.995 inches and 1.005 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 3.035 inches and 3.045 inches

Distance From Mounting Shoulder To Front Face:

Between 0.115 inches and 0.135 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

45 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

30.0 2nd mating end 1st contact grouping

Polarization Method:

2 polarization posts

Shell Type:

Solid

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

12

Thread Size:

0.3125 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic silicone single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

43 2nd mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.090 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0