Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-451-5716

Thread Class:
2b Three d Direction
Thread Direction:
Right-hand
Body Style:
Straight shape, flush mount
Overall Length:
Between 1.490 inches and 1.510 inches
Overall Height: Between 4.615 inches and 4.635 inches
Overall Width:
Between 3.365 inches and 3.385 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.995 inches and 1.005 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 3.035 inches and 3.045 inches
Distance From Mounting Shoulder To Front Face:
Between 0.115 inches and 0.135 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
45 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
30.0 2nd mating end 1st contact grouping
Polarization Method:
2 polarization posts
Shell Type:
Solid
Connector Locking Method:
Screw
Thready Qty Per Inch (tpi):
12
Thread Size:
0.3125 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings



Contact Surface Treatment: Gold single mating end all contact groupings **Insert Material:** Plastic silicone single mating end **Terminal Type:** Solder well single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 43 2nd mating end 2nd contact grouping Included Contact Type: Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.090 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0