NSN 5935-00-451-5754

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5035-00-451-5754

view Online at https://aerobasegroup.com/nsn/5935-00-451-5754
Body Style:
Straight shape, internal coupling
Overall Length:
0.965 inches
Overall Diameter:
0.450 inches
Environmental Protection:
Moisture resistant and vibration resistant
Cable Entrance Diameter:
Between 0.145 inches and 0.155 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
120.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper single mating end single
contact grouping

contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c or d, cl 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530, cond h, at or ht federal specification single material response single mating end single contact grouping

NSN 5935-00-451-5754Electrical Plug Connector - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Shell Material Specification:
Qq-w-423, comp 302, cond b federal specification single material response
ncluded Contact Quantity:
1 single mating end single contact grouping
ncluded Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
4039b0
Mil-std (military Standard):
Mil-g-45204 spec.