## NSN 5935-00-451-7392

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-451-7392 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.340 inches **Overall Height:** Between 1.969 inches and 2.031 inches **Overall Width:** Between 1.969 inches and 2.031 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.157 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.557 inches and 1.567 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.557 inches and 1.567 inches **Distance From Mounting Shoulder To Front Face:** Between 0.812 inches and 0.843 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-13 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

## NSN 5935-00-451-7392

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
1.750 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.026 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0