

View Online at <https://aerobasegroup.com/nsn/5935-00-452-0596>

**Body Style:**

Straight type

**Overall Length:**

2.850 inches

**Overall Height:**

0.690 inches

**Overall Width:**

0.250 inches

**Environmental Protection:**

Moisture resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Distance Between Mounting Facility Centers:**

2.600 inches

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end 1st contact grouping

**Polarization Method:**

Guide pin/socket

**Terminal Location:**

Back single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end 1st contact grouping

**Terminal Type:**

Solder well single mating end 1st contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response or qq-b-750 federal specification single material response single mating end 1st contact grouping

**Included Contact Quantity:**

20 single mating end 1st contact grouping

**Included Contact Type:**

Round socket single mating end 1st contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.020 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.