

View Online at <https://aerobasegroup.com/nsn/5935-00-452-1205>

**Body Style:**

Straight shape

**Overall Length:**

1.685 inches

**Overall Height:**

4.325 inches

**Overall Width:**

1.170 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 3.871 inches and 3.879 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.458 inches and 0.566 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.615 inches and 0.630 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

71c15 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

7.5 single mating end 2nd contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy a380.0

**Shell Surface Treatment:**

Cadmium

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Included Contact Quantity:**

56 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end 2nd contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.071 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0