# NSN 5935-00-454-3306

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-454-3306

#### Body Style:

Straight shape, internal coupling w/strain relief

#### **Body Length:**

1.812 inches

## **Overall Diameter:**

1.391 inches

### **Environmental Protection:**

Moisture resistant

#### Cable Entrance Diameter:

Between 0.600 inches and 0.635 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

18-66 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

400.0 single mating end single contact grouping

# Contact Maximum Dc Voltage Rating In Volts:

550.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

0.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet latch

#### **Connector Cable Strain Relief Method:**

Cable clamp

#### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## Insert Material:

Plastic epoxy single mating end and glass fiber single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# NSN 5935-00-454-3306

Electrical Plug Connector - Page 2 of 2



Terminal Type:	
	ing end single contact grouping
Shell Material:	
Aluminum alloy	
Shell Surface Tr	
Cadmium and nic	
	eatment Specification:
Qq-p-416 federal	specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response
Included Contac	t Quantity:
66 single mating	end single contact grouping
Included Contac	et Type:
Round socket sin	gle mating end single contact grouping
Precious Materia	al And Location:
Contact surfaces	gold
Precious Materia	al And Weight:
0.066 gold grains	, troy
Precious Materia	al:
Gold	
Shelf Life:	
N/a	
Unit Of Measure	:
Demilitarization	
No	
Fiig:	
A039b0	
Mil-std (military	Standard):
Mil-g-45204 spec	