## NSN 5935-00-454-6876

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-454-6876 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.344 inches **Overall Height:** 0.531 inches **Overall Width:** 0.375 inches **Unthreaded Mounting Hole Diameter:** 0.086 inches **Distance Between Mounting Facility Centers:** 1.094 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 29 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 180.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Screw lock pin Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end

Plastic diallyl pht
Terminal Type:

Solder well single mating end single contact grouping

## NSN 5935-00-454-6876

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-19833, ty gdi-30 military specification single material response single mating end

**Included Contact Quantity:** 

29 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.