

View Online at <https://aerobasegroup.com/nsn/5935-00-454-7089>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

Between 1.420 inches and 1.460 inches

**Overall Diameter:**

Between 0.670 inches and 0.710 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration resistant

**Cable Entrance Diameter:**

Between 0.170 inches and 0.180 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.670 inches and 0.680 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

130.0 and 230.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Compression nut

**Thread Size:**

0.500 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533, comp 172 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold and copper alloy

**Shell Surface Treatment Specification:**

Mil-g-45204, type 2, class i military specification single treatment response

**Shell Material Specification:**

Qq-b-626, comp 22, 1/2 hard federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Triaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and shell surface gold

**Precious Material And Weight:**

0.105 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.