

View Online at <https://aerobasegroup.com/nsn/5935-00-454-7090>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.420 inches and 1.460 inches

Overall Diameter:

Between 0.670 inches and 0.710 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration resistant

Cable Entrance Diameter:

Between 0.170 inches and 0.180 inches

Distance From Mounting Shoulder To Front Face:

Between 0.670 inches and 0.680 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

110.0 and 250.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Compression nut

Thread Size:

0.506 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-533, comp 172 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and copper alloy

Shell Surface Treatment Specification:

Mil-g-45204 type 2, class @i military specification single treatment response

Shell Material Specification:

Qq-b-626, comp 22, 1/2 hard federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Triaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and shell surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.