NSN 5935-00-454-8324

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-454-8324

Body Style: Straight shape w/flange **Overall Length:** 1.604 inches **Overall Height:** Between 1.802 inches and 1.823 inches **Overall Width:** Between 1.802 inches and 1.823 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.152 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Distance From Mounting Shoulder To Front Face:** Between 0.507 inches and 0.602 inches Mating End Quantity: 2 **Contact Maximum Current Rating In Amps:** 7.5 2nd mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 all mating ends all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 850.0 all mating ends all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** Aircraft, eagle f-15 **Contact Material:** Copper alloy all mating ends all contact groupings **Contact Surface Treatment:** Gold all mating ends all contact groupings and silver all mating ends all contact groupings **Criticality Code Justification:**

Feat

NSN 5935-00-454-8324

Connector Adapter - Page 2 of 2



Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Included Contact Type:

Round socket 2nd mating end all contact groupings

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

 $0.112 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.112 \ \text{silver grains}, \ \text{troy}$

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0