

View Online at <https://aerobasegroup.com/nsn/5935-00-455-0868>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Rectangular shape w/hood side opening, w/jackscrew

**Overall Length:**

1.655 inches

**Overall Height:**

2.144 inches

**Overall Width:**

0.686 inches

**Cable Entrance Diameter:**

0.454 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

8.5 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Shell Type:**

Hood, side opening

**Connector Locking Method:**

Jackscrew

**Connector Cable Strain Relief Method:**

Cable clamp

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Guide Design And Location:**

Key shape pin right-hand at 9 oclock

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Enamel

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:**

20 single mating end single contact grouping

**Included Contact Type:**

Hermaphrodite single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.020 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.