## NSN 5935-00-455-4500

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-455-4500

Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.812 inches
Overall Diameter:
1.141 inches
Environmental Protection:
Moisture resistant

**Cable Entrance Diameter:** 

Between 0.350 inches and 0.385 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

14-35 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

400.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

550.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet latch

**Connector Cable Strain Relief Method:** 

Cable clamp

**Operating Tempurature Rating:** 

Between -65.0 degrees celsius and 200.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **NSN 5935-00-455-4500**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and nickel
Shell Surface Treatment Specification:
Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.