NSN 5935-00-456-4709

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-456-4709 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 1.965 inches **Overall Height:** 2.390 inches **Overall Width:** 2.875 inches **Environmental Protection:** Heat resistant and pressure proof and vibration proof and watertight **Unthreaded Mounting Hole Diameter:** 0.149 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.850 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.500 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 212 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1800.0 single mating end single contact grouping **Polarization Method:** Polarization boss **Shell Type:** Solid **Connector Locking Method:** Jackscrew Thready Qty Per Inch (tpi): 28

Thread Size:

0.250 inches

NSN 5935-00-456-4709

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Insert Material Specification:
Mil-m-19833, ty gdi-30f or mil-m-14, ty sdg-f military specification 1st material response and mil-m-19833, ty gdi-30f or mil-m-14, ty sdg-f
military specification 2nd material response and I-p-395 federal specification 3rd material response single mating end
Included Contact Quantity:
212 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.212 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.