

View Online at <https://aerobasegroup.com/nsn/5935-00-456-9052>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

Between 4.328 inches and 4.360 inches

**Overall Height:**

0.656 inches

**Overall Width:**

Between 0.318 inches and 0.338 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.111 inches and 0.121 inches

**Distance Between Mounting Facility Centers:**

Between 4.026 inches and 4.036 inches

**Board Accommodated Length:**

3.573 inches single board and 3.583 inches single board

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bridged contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Fixed inter-contact

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy 172 single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533, alloy 172 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

22 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.022 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.