

View Online at <https://aerobasegroup.com/nsn/5935-00-457-5632>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

Between 0.781 inches and 0.943 inches

**Overall Diameter:**

Between 1.297 inches and 1.327 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Distance From Mounting Shoulder To Front Face:**

0.675 inches

**Mounting Facility Thickness:**

0.108 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

27-30 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.625 inches

**Insert Material:**

Plastic phenolic single mating end

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shell Material Specification:**

Qq-a-225/5 federal specification single material response

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Bushing Accommodation Hole Shape:**

Round w/flat

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.