NSN 5935-00-457-5650

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-457-5650

Body Style:

Straight shape, internal coupling

Overall Length:

Between 0.782 inches and 0.844 inches

Overall Diameter:

Between 1.184 inches and 1.214 inches

Environmental Protection:

Corrosion resistant and vibration resistant and moisture resistant and heat resistant and cold resistant and thermal shock resistant and

pressure proof

Mating End Quantity:

1

Contact Position Arrangement Style:

19-33 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

NSN 5935-00-457-5650

Electrical Plug Connector - Page 2 of 2



Shell Material Specification: Mil-c-26482 military specification single material response **Insert Material Specification:** Mil-m-14f, ty mfh military specification single material response single mating end **Included Contact Quantity:** 61 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.061 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.